



Workshop Equipment & Service

GIULIANO S228PRO DUO LEVERLESS TYRE CHANGER

Features:

- Tilting tower, sliding horizontal arm with 41 mm operating arm
- Bead breaker double effect Cylinder 200mm
- Reinforced Chassis and tower
- Equipped with Lever - No Lever tyre mounting/demounting system (Giuliano Patent);
- Tabletop thickness 14 mm w/adjust jaws (Giuliano Patent)
- Tyre inflation by pedal (standard)
- Suitable for tubeless tyre beat seating system (Optional)
- "Easy Access" extractable pedal box for quick service;
- PO System, Giuliano patent, for granting no BB shovel stuck into the rim;
- Robotic pipe for operating arm positioning/lock



Specifications:

- Rim clamping from outside 10-26 "
- Rim clamping from inside 12-24 "
- Max. tyre diameter 1100mm
- Max. tyre width 415mm
- Bead breaker cylinder force at 10 bar 30800 N
- Operating pressure 10 bar
- Power Supply Voltage. 400V - 3ph / 2 Speed 220V - 1ph 220V 1ph / 2 speed
- Motor power 0.8/1.1 kW (3ph)
- Rotation speed 7-14 rpm
- Pre-set tyre inbating pressure 3.5 Bar (50 Psi)
- Net weight 409kg
- Max overall dimensions 1950 x 1890 x 2160 mm

