



Workshop Equipment & Service

## POWERLIFT PLC-802A TRUCK TYRE CHANGER

### Features:

- Meet CE requirement, safe during operation
- The lifting arm oil tank is equipped with double safety protection which improves the safety of the operation
- Fully automatic tyre change adopts pneumatic and hydraulic power control system to improve efficiency and labor saving
- The hydraulic pump station adopts imported components with stable performance
- The gear box is made of aluminium alloy die casting with light weight, good sealing performance
- Movable operating station can be fully observed during operation to prevent danger from misoperation
- Dual speed main shaft motor can improve the working efficiency
- The fully automatic demounting arm can move up and down, back and forth freely.
- Equipped with the hydraulic driven carriage making the tyre moving on the tyre changer without manpower



### Specifications:

- Rim diameter: 14"-46"
- Rim range with extension: 46"-56"
- Rim width: 1100mm
- Max wheel diameter: 2200mm
- Hydraulic power: 130-150 bar
- Hydraulic station motor power: 1.5kw 380V/3PH 50Hz
- Main shaft motor power: 2.4/3.0kw 380V/50Hz 3Ph
- Noise: <75DB
- Packing dimension: 2280x2070x1100mm
- Net weight/Gross weight: 987/1283kg
- Loading in 20'/40/ container: 4/10 sets

