



Workshop Equipment & Service

# POWERLIFT PLC-502A TYRE CHANGER WITH TILT ARM

## Features:

- Tilt back column with assisting arm
- Turntable protective covers as standard protect the rim from scratched by turntable and the ruler on the covers can help to clamp the rim conveniently.
- The wearable washers as standard correspond to Europe standard to protect the personal safety when mounting the tire.
- The control pedal assembly has the step-move function which can stop the clamp at any position to clamp the rim conveniently.
- The hexangular shaft with 41mm and S 55 horizontal arm diameter is suitable for operation the flat and hard tire.
- The machine adopts the parkerising bead breaker cylinder having bead break power 2500KG to bead break the tire from rim easily.
- The machine equips the protective cover for clamps and mounting head as standard configuration to avoid damage the rim.
- The clamp is made of special material, strong and durable.
- The mounting head is made of special steel and lifetime warranty.
- 1 standard equip inflation meter and safety valve,controllable air pressure, protection for safety.



## Specifications:

- Outside Clamp 10-20 "
- Tire Width 3-12 "
- Inside Clamp 12-23 "
- Max Wheel Diameter 1120 mm
- Working air pressure 8-10bar
- Turntable Rotation Speed 6.5rpm
- Power Supply Voltage. 220V/380V
- CTN.size. 1100 x910 x1010mm+1280x550 x450mm
- Power 0.75/1.1 kw
- Noise <70dB
- Net weight 246+72kg
- Gross weight 285+95kg
- Container Loading Quantity 40 units

