



Workshop Equipment & Service

POWERLIFT PLC-501 SWING ARM TYRE CHANGER

Features:

- Entry level swing arm tyre changer
- Turntable protective covers as standard protect the rim from scratched by turntable and the ruler on the covers can help to clamp the rim conveniently.
- The wearable washers as standard correspond to Europ standard to protect the personal safety when mounting the tire.
- The control pedal assembly has the step-move function which can stop the clamp at any position to clamp the rim conveniently.
- The hexangular shaft with 41mm and S 55 horizontal arm diameter is suitable for operation the flat and hard tire.
- The machine adopts the parkerising bead breaker cylinder having bead break power 2500KG to bead break the tire from rim easily.
- The machine equips the protective cover for clamps and mounting head as standard configuration to avoid damage the rim.
- The clamp is made of special material, strong and durable.
- The mounting head is made of special steel and lifetime warranty.
- Standard equip inflation meter and safety valve,controllable air pressure,protection for safety.



Specifications:

- Outside Clamp 10-18 "
- Tire Width 3-12 "
- Inside Clamp 12-21 "
- Max Wheel Diameter 960mm
- Working air pressure 8-10bar
- Turntable Rotation Speed 6.5rpm
- Power Supply Voltage. 220V
- CTN.size. 980 x 760 x 870 mm
- Power 0.75
- Noise < 70dB
- Net weight 183kg
- Gross weight 203kg
- Container Loading Quantity 34 units/20'

