



## GEODYNA 7600L WHEEL BALANCER



### FEATURES

- High-productivity wheel balancer
- Touchscreen monitor with graphical user interface GOLD – improved intuitiveness and ergonomics
- easyWeight laser light indicator for fast, accurate and pinpoint placement of adhesive weights on the wheel
- Semi-automatic input of offset and rim diameter via 2D SAPE and automatic rim width acquisition via Smart Sonar
- Semi-automatic pre-selection of balancing mode via easyAlu
- Rim lighting to facilitate rim cleaning and speed up data entry and weight positioning
- New ergonomic weight tray
- Imbalance minimisation and optimisation programs
- VPM measurement technique for uncompromised accuracy
- QuickBal for reduced measurement time:  
Short start-stop cycle time: 4.5 seconds (15" rim)
- Clamping of wheel on integrated flange with quick nut

### SPECIFICATIONS

<b>Motorised</b>	Yes
<b>Wheel Clamping</b>	Quick Nut
<b>Measuring Speed</b>	< 200 rpm
<b>Balancing Accuracy</b>	1 g (0.035 oz)
<b>Angular Resolution</b>	± 0,35°
<b>Length of Shaft</b>	225 mm
<b>Start/Stop balance time - Check spin</b>	4 s
<b>Rim Diameter Range</b>	8" - 32"
<b>Offset Range</b>	1" - 20"
<b>Rim Width Range</b>	1" - 20"
<b>Max. Wheel Diameter</b>	1050 mm
<b>Max. Wheel Weight</b>	70 Kg
<b>Input Power (VAC)</b>	230 VAC 1ph 50/60 Hz
<b>Dimensions LxWxH</b>	1383 x 878 x 1834
<b>Weight</b>	140 Kg

CALL LOGICAR FOR MORE INFORMATION

☎ 1300 322 782