



GEODYNA 7600P WHEEL BALANCER



FEATURES

- With torque-controlled Power Clamp device instead of quick nut
- High-productivity wheel balancer
- Touchscreen monitor with graphical user interface GOLD – improved intuitiveness and ergonomics
- easyWeight laser light indicator for fast, accurate and pinpoint placement of adhesive weights on the wheel
- Semi-automatic input of offset and rim diameter via 2D SAPE and automatic rim width acquisition via Smart Sonar
- Semi-automatic pre-selection of balancing mode via easyAlu
- Rim lighting to facilitate rim cleaning and speed up data entry and weight positioning
- New ergonomic weight tray
- Imbalance minimisation and optimisation programs
- VPM measurement technique for uncompromised accuracy
- QuickBal for reduced measurement time:
Short start-stop cycle time: 4.5 seconds (15" rim)

SPECIFICATIONS

Motorised	Yes
Wheel Clamping	Power Clamp
Measuring Speed	< 200 rpm
Balancing Accuracy	1 g (0.035 oz)
Angular Resolution	± 0,35°
Length of Shaft	225 mm
Start/Stop balance time - Check spin	4 s
Rim Diameter Range	8" - 32"
Offset Range	1" - 20"
Rim Width Range	1" - 20"
Max. Wheel Diameter	1050 mm
Max. Wheel Weight	70 Kg
Input Power (VAC)	230 VAC 1ph 50/60 Hz
Dimensions LxWxH	1383 x 878 x 1834
Weight	140 Kg

CALL LOGICAR FOR MORE INFORMATION

☎ 1300 322 782